



Kenmore 50 Gallon Medium Height Power Miser 6 Electric Water Heater

42-32666

- Factory-installed temperature and pressure safety valve
- Limeguard elements resist lime build-up and lasts longer than standard elements
- DualWatt lower element easily converts from 3,800 to 5,500 Watt operation to fit the customer's wiring
- Cobalt Blue Ultra Coat Glass-Lined tank with single anode rod for tank protection
- Energy efficient foam insulation
- Roto-Swirl self-cleaning cold water inlet tube

Selection	42-32666
<b>Features</b>	
Tank Capacity	50 Gallons
Number of Elements per Unit	2
Upper Element Type	Limeguard
Lower Element Type	Limeguard DualWatt
Anode	1
Dip Tube	PEX Roto-Swirl
Tank Material	Glass-Lined Steel
Insulation Material	Foam
Insulation R Value	16
Insulation Depth (Inches)	2
Recovery at 90 Degree Rise	17.3 G.P.H. @ 3,800W 25 G.P.H. @ 5,500W
First Hour Rating	59 Gallons @ 3,800W 62 Gallons @ 5,500W
Voltage	240 Volts
Kilowatt Hrs. Per Year	4,721
Wattage at 240V	5,500 Watts
Maximum Fuse Required	30 Amps
Minimum Wire Size	10 Gauge
Alternate Dual Power	
Wattage at 240V	3,800 Watts
Maximum Fuse Required	20 Amps
Minimum Wire Size	12 Gauge
Est. Yearly Operating Cost	\$503
Shipping Weight (Approx. Lbs.)	145
<b>Dimensions (Inches)</b>	
Maximum Height	49
Height	49
Width	23
Depth	23
Diameter	23
<b>Warranty</b>	
1-Year Limited Warranty – Entire Appliance	Labor
6-Year Limited Warranty	Tank & Parts

If used for other than private family purposes, warranty applies for only 2 years.